



HQ-004/HQ-006

Specifications

Enclosure	Weatherproof IP67
Power supply	110/220v 50/60Hz, 24vAC/DC
Duty cycle (On/Off Duty)	S2 35%
Motor	Reversible motor
Limit switches	2 x SPDT, 250V AC 3A
Additional limit switches	2 x SPDT, 250V AC 3A
Space heater	2W (110/220V AC)
Manual override	Hexagon
Conduit entries	2 x M20
Movement angle	320° ± 10° (0° to 320°)
Ambient temperature	-20°C to 70°C
External coating	Dry power, Polyester

Option Specifications

Enclosure	Weatherproof IP68
Conduit entries	2 x PG 13.5. 1/2" NPT
Potentiometer unit	1K – 10K
Proportional control unit	I/Out: 0-10V, 4-20mA DC
Current position transmitter	Output 4-20mA DC
Local control unit	Remote/Open/Stop/Close s/w

Article no.	Voltage	Torque Nm	Mounting Details	Price £	Price €
HQ004A	240V- AC	40	F03/F05/F07 14mm STAR	£342.40	€428.00
HQ004B	110V - AC	40		£342.40	€428.00
HQ004D	24V - DC	40		£358.40	€448.00
HQ006A	240V- AC	60		£528.00	€660.00
HQ006B	110V - AC	60		£528.00	€660.00
HQ006D	24V - DC	60		£547.20	€684.00
HQ006PCU*	110V - 220V	60		£1,292.80	€1,616.00

* with in-built PCU 4-20mA/0-10V Positioner

Performance

MODEL	MAX OUTPUT TORQUE	OPERATING TIME 50/60Hz	MOTOR CLASS E FRAME SIZE	RATED CURRENT (A)				WEIGHT
				AC 1PH. 50/60Hz		DC		
		90°	W* F	24V	110V	220V	24V	Kg
HQ-004	40Nm	14/12 Secs.	6* 70	0.3	0.39/0.4	0.19/0.2	0.2	3
HQ-006	60Nm							

Dimensions

