



3 Way Electrically Actuated Stainless Steel Ball Valve 'L' & 'T' Bore

1,000 PSI Rated - 1/4" to 2"

800 PSI Rated - 2 1/2" to 4"

Article no. L bore	Article no. T bore		Size	Actuator Size	Price £	Price €
399061*	399071*		1/4"	HQ005	£528.40	€634.10
399062*	399072*		3/8"	HQ005	£530.40	€636.50
399063*	399073*	* Suffix with: A = 220v AC B = 110v AC D = 24v DC	1/2"	HQ005	£520.40	€624.50
399064*	399074*		3/4"	HQ005	£545.00	€654.00
399065*	399075*		1"	HQ005	£594.30	€713.10
399066*	399076*	Others on request	1 1/4"	HQ005	£679.40	€815.20
399067*	399077*		1 1/2"	HQ005	£863.10	€1,035.70
399068*	399078*		2"	HQ006	£1,220.40	€1,464.40

Materials

Body	CF8M - 316 Stainless Steel
Ball	316 Stainless Steel
Stem Seal	PTFE
Ball Seal	PTFE
Temp. Range	+70°C*

Specifications - HQ005 Actuator

Enclosure	Weatherproof enclosure IP67
Power supply	85 - 265 VAC 1 ph, 50/60 Hz 24 VAC/DC
Duty cycle	S4: 70% (average load of 80% Max. torque) S2: 50% (average load of 80% Max. torque)
Motor	BLDC motor
Limit switches	2 x open/close, SPDT, 250 V ac 10 A rating
Additional limit switches	2 x open/close, SPDT, 250 V ac 10 A rating
Anti-condensation board	2 W
Manual override	Manual Handwheel
Cable entries	Standard: 2 x M20
Movement angle	320 ± 10° (0 - 330°)
Ambient temperature	-20 to +80 °C

Dimensions (mm) - HQ005 Actuator

